

# PRIJS LIJST of SR Series (CE, UL, RoHS)

<b>ARRAY ELECTRONIC CO LTD</b> Touwslagerij 19 4762 at Zevenbergen http://www.motion.nl		<b>Company Name</b>	<b>Company Logo</b>
<b>Contact:</b> G v Weas <b>Email:</b> sales@motion.nl <b>Pho:</b> +31 0168 325077 <b>Fax:</b> +31 0168 328134 <b>GSM:</b> +		<b>Contact:</b> <b>Email:</b> <b>Pho:</b> <b>Fax:</b>	

<b>Expiry date:</b> 2008-06-30	<b>FOB Zevenbergen</b>
--------------------------------	------------------------

Code	Mode	Power Supply	Specifications	Unit Price (euro)
AC101	SR-12MRAC	100~240VAC	8 AC IN/ 4 RELAY OUT	72.00
AC102	SR-12MRDC	12~24VDC	8 DC IN (A)/ 4 RELAY OUT	72.00
AC103	SR-12MTDC	12~24VDC	8 DC IN (A)/ 4 TRANSISTOR OUT (NPN)	72.00
AC104	SR-12MGDC	12~24VDC	8 DC IN (A)/ 4 TRANSISTOR OUT (PNP)	72.00
AC105	SR-22MRAC	100~240VAC	14 AC IN/ 8 RELAY OUT	112.00
AC106	SR-22MRDC	12~24VDC	14 DC IN (A)/ 8 RELAY OUT	112.00
AC107	SR-22MTDC	12~24VDC	14 DC IN (A)/ 8 TRANSISTOR OUT (NPN)	112.00
AC108	SR-22MGDC	12~24VDC	14 DC IN (A)/ 8 TRANSISTOR OUT (PNP)	112.00
AC109	SR-20ERA	100~240VAC	12 AC IN/ 8 RELAY OUT	84.00
AC110	SR-20ERD	12~24VDC	12 DC IN (A)/ 8 RELAY OUT	84.00
AC111	SR-20ETD	12~24VDC	12 DC IN (A)/ 8 TRANSISTOR OUT (NPN)	84.00
AC112	SR-20EGD	12~24VDC	12 DC IN (A)/ 8 TRANSISTOR OUT (PNP)	84.00



### ACCESSORIES

AC113	SR-RCA	100~240VAC	Receiver module	110.00
AC114	SR-RCD	12~24VDC	Receiver module	110.00
AC115	SR-TC	DC3V	Transmitter module	56.00
AC116	SR-EANT	Lengthened antenna for SR-RCA/ RCD		44.00
AC117	SR-VPA	100~240VAC	Voice module for telephone control	100.00
AC118	SR-VPD	12~24VDC	Voice module for telephone control	100.00
AC119	SR-AUD	Wire between PC Audio Card and SR-VPA/ VPD		2.00
AC120	SR-HMI-L	Human Machine Interface with Keypad (LCD Display)		20.00
AC121	SR-HMI-B	Human Machine Interface with Keypad (LCD Display with backlight)		22.00
AC122	SR-WRT	Removable Programming Panel with Keypad		20.00
AC123	SR-EHC	Lengthened interface between SR and HMI for remote monitoring		14.00
AC124	SR-CP	Interface between SR (Side) and PC for programming and monitoring		18.00
AC125	SR-DCP	Interface between SR (Front) and PC for programming and monitoring		18.00
AC126	SR-USB	USB/ RS232 Converter (DIN installation)		30.00
AC127	SR-DUSB	Interface between SR and PC USB port		22.00
AC128	SR-CBA	Connection Bridge between Main and Expansion block (for AC Type)		Free
AC129	SR-CBD	Connection Bridge between Main and Expansion block (for DC Type)		Free
AC130	SR-ECBA	Lengthened Connection Bridge between Main and Expansion block (for AC Type)		8.00
AC131	SR-ECBD	Lengthened Connection Bridge between Main and Expansion block (for DC Type)		8.00

\* (A): Input can be used as Analog input of 0~10VDC, 0.1VDC increment, 7 bits resolution.

\* Different range of discount is given according to the order quantity.

# PRIJS LIJST of SP (CE, RoHS)

<b>Motion Control Systems</b> Touwslagerij 19 4762 at Zevenbergen <a href="http://www.motion.nl">http://www.motion.nl</a>			company name	company logo
Contact: G v Waes Email: <a href="mailto:sales@motion.nl">sales@motion.nl</a> Pho: +31 0168 325077 Fax: +31 168 328134 GSM: +			Contact: Email: Pho: Fax:	
<b>Expiry date: 2008-06-30</b>		<b>FOB Zevenbergen</b>		
Code	Mode	Quantity (Pcs)	Unit Price (euro)	
AC301	SP-05AS	1-99	30.00	
AC302	SP-12AS	100~	26.00	
AC303	SP-24AS			
AC304	SP-05AL	1-99	54.00	
AC305	SP-12AL	100~	48.00	
AC306	SP-24AL			

## Specifications:

Model	SP-05AS	SP-12AS	SP-24AS	SP-05AL	SP-12AL	SP-24AL
Full-range Voltage Input	100-240VAC/ 140-340VDC					
Allowable Voltage Range	85-264VAC/ 120-370VDC					
Output Voltage*	5V	12V	24V	5V	12V	24V
Output Current	6A	3A	1.5A	10A	6A	3A
Size (L×W×H)	71mm×106mm×65mm			126mm×106mm×65mm		
<b>Note:</b> Models of higher output voltage range such as 48VDC can be offered according to user's request.						